



NOTES

1. 50MM NOMINAL BORE GALVANISED STEEL POLE TO AUSTRALIAN STANDARD 1742 WITH GALVANISED CAP.
2. 600MM SIDE-WIND SPIKE.
3. POLE TO BE 2.8m HIGH, OR 3.2m HIGH IF THERE ARE 3 OR MORE SIGNS ON THE POLE.
4. DOUBLE WEDGES IN SLEEVE.
5. ANTI-VANDAL BOLTS TO BE USED TO AFFIX SIGN.
6. SIGN BACKGROUND COLOUR: WHITE (ENGINEERING GRADE 2 REFLECTORISATION).
7. TEXT COLOUR: GRAPE (PL CODE: 5265).
8. TEXT HEIGHT 100MM (SERIES 'D' AS SPECIFIED IN AS1744).
9. LOGO BACKGROUND: YELLOW.
10. LOGO SHELL OUTLINE: GRAPE (PL CODE: 5265).
11. SIGN TO BE CONSTRUCTED TO AS 1742.5.
12. DIMENSIONS OF SIGN AS PER AS 1742.5.
13. ALL DIMENSIONS ARE IN MILLIMETRES.



STANDARD PLAN
STREET SIGN

CERTIFICATION

D. Rotter
DEREK ROTTER - MANAGER PROJECT DELIVERY

DATE OF ISSUE: Sept 2015

SHEET NO.: 1 OF 1

MP812